

EXPLOSIONSZEICHNUNG



KBS Gastrotechnik GmbH – Schoßbergstraße 26 – 65201 Wiesbaden

PG-SA / PG-2SA PART LIST

S/N	Description (English)	Material	Part Code	Unit QTY
1	Power indicator	250V/16A, green	70101300046	2
2-1	Thermostat	50-300°C/250V,16A	70100300246	2
2-2	Thermostat Knob with base	ABS \varnothing 40.5 (A04) ; 50-300°C	70101100464+70101100091	2
3	Cross head screw	Galvanized M4×6/A3		4
4	Heating indicator	250V/14A, yellow	70101300055	2
5	Bottom body	304 δ =0.8mm		1
6	Socket head screw	M6×10 45#Oxide passivation		4
7	Flat shim	ϕ 18× ϕ 6.5×1.5 A3 Galvanized		4
8	Socket head screw	M5×25 45#Oxide passivation		2
9	Flat shim	ϕ 18× ϕ 6.5×1.5 A3 Galvanized		2
10	Torsion spring	65Mn steel wire ϕ 3.5	70200800273	2
11	Back Rotation shaft	Cold-drawn steel pipe ϕ 14×1.5	70200402391	2
12	Holding stand	Brass 35×15×13	70202001373	2
13	Socket head screw	M6×40 45#Oxide passivation		4
14	Back top shield	304 δ =0.8mm		1
15	Cross head screw	M4×8 A3 chrome plating		1
16	Elastic cylinder pin	ϕ 4×40, 65Mn		2
17	Equipotential grounding screw	M6×15 brass		1
18	Wire jacket	ϕ 16 heat-resisting plastic		1
19	Power cord	250V		1
20	Power grounding screw	M5×15 brass		1
21	Bottom plate	Cast iron	70200101855	1
22	Top cover	304 δ =0.8mm		2
23	Cross head screw	M4×8 A3 Chrome plated		8
24	Upper heat insulation cotton	Fiberglass		1
25	Heating element pressure plate	Galvanized sheet δ =1.0mm		2
26	Top plate	Cast iron	70200101837+70200101846	1
27	Top heating element	230V 0.8kW SS pipe ϕ 6	70100400264	2
28	Leading-in pipe	Cold-drawn steel pipe ϕ 14×1.5	70202011255	2
29	Axial circlip	65Mn ϕ 12		4
30	Pipe circlip	65Mn ϕ 14		4
31	Shaft bearing for top cover	Cold-drawn round steel ϕ 12×386 chrome plated		2
32	Socket head screw	M5×16 45#O chrome plating		4
33	Socket head screw	M6×8 45#O chrome plating		4

34	Handle sleeve	Bakelite $\phi 30 \times 262 \text{mm}$	70200700491	2
35	Handle frame	A3 steel $280 \times 350 \times 20$	70200701919	2
36	Oil collector	$304\delta = 0.8 \text{mm}$		1
37	Lower heat insulation cotton	Fiberglass		1
38	Pressure plate for cotton	Zinc plating $\delta = 0.8 \text{mm}$		1
39	Cross head screw	M4 \times 20 A3 chrome plating		2
40	Terminal board	430 $\delta = 1.0 \text{mm}$		1
41	Cross head screw	M4 \times 8 A3 chrome plating		8
42	Terminal ceramic	Heat resisting ceramic 500V, 15A	70100700528	1
43	Temperature Limiter	130 $^{\circ}\text{C}/250\text{V}, 16\text{A}$	70100300337	2
44	Hexagonal head screw	M6 \times 20/A3 chrome plating		4
45	Rubber foot	$\phi 30 \times 15$ rubber black	70200900273	4
46	Lower heating element pressure plate	Galvanized sheet $\delta = 1.0 \text{mm}$		2
47	Lower heating element	230V 1.0kWSS pipe $\phi 6$	70100400273	2
48	Socket head screw	M6 \times 8 45# chrome plating		8
49	Bottom plate	Galvanized sheet $\delta = 0.8 \text{mm}$		1
50	Cross head screw	M4 \times 8 A3 chrome plating		6



